





**Product Family**  
**XTP™ PVC Footwear**

- XTP™ is engineered with chemical resistance formulation
- Seamless, 3-stage, PVC injection molded construction is 100% waterproof
- TDT outsole compounds are formulated for long wear reducing cost of inventory and slip resistance
- Engineered outsole has a dual compound
- Steel toe protection



**Product Numbers & Ordering Information**

	Product Numbers	Details
	75108	<b>Servus®, XTP®, PVC, TDT Technology Footwear, Plain toe</b> Boot – XTP® – PVC – 15 in (38.1 cm) – Black/Red/Gray – Plain toe – extended ribbed steel shank – removable and washable ergonomic insoles – Men's whole sizes: 3 - 15
	75109	<b>Servus®, XTP®, PVC, TDT Technology Footwear, Steel toe</b> Boot – XTP® – PVC – 15 in (38.1 cm) – Black/Yellow/Gray – "Safe-Toe" steel toe – extended ribbed steel shank – removable and washable ergonomic insoles – Men's whole sizes: 3 - 15

**Packaging Information**

1 pair per bag, 6 pair per case

**Hazardous Materials**

NA

**Overview**

**Key Features**

- XTP™ is engineered with reinforced construction and chemical resistance formulation to provide superior protection in harsh environments
- Seamless, 3-stage, PVC injection molded construction is 100% waterproof to keep feet comfortable and dry
- TDT outsole compounds are formulated for long wear and slip resistance, reducing the cost of inventory and injury
- Engineered outsole has a dual compound, durable exterior for abrasion and harsh conditions and a softer interior for comfort and excellent traction to prevent slips and falls
- Removable FOOT FORM contour cushion insoles provides support for comfort and wicks away moisture to keep workers' feet dry
- Higher, wider, kick-off lugs for easy on/off convenience

**Recommended Industries/Use**

- Agriculture
- Chemical
- Government
- Military
- Municipal Services
- Oil and Gas
- Utilities
- Nuclear

**Hazards**

- Abrasion
- Chemical
- Impact
- Slip
- Splash

**Regulations**

- American Society of Testing and Materials - ASTM F2413-11
- ANSI Z41-1991 - OSHA 1910.136 states; The employer shall ensure that each affected employee uses protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or objects piercing the sole, and where such employee's feet are exposed to electrical hazards. For more information go to [www.osha.gov](http://www.osha.gov).
- Canadian Standards Association - CAN/CSA Z195-09

**Historical Brand**

Norcross Safety Products

**Warranty Information**

Each new Product manufactured and/or sold by NSP is warranted to be free from defects in material and/or workmanship. NSP's responsibility is limited to, at its option repairing or replacing any instrument or part thereof, or issuing a credit, for a period of one year after shipment. NSP's warranty sets forth the limit of NSP's responsibility. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS, ARE EXCLUDED

**Specifications**

**Construction**

- Cut and sewn

**Construction**

- Injection molded

**Height**

- 15 inch (38.1 cm)

**Height**

- NA

**Insole**

- Foot Form

**Insole**

- NA

**Insulated**

- NA

**Insulated**

- No

**Material**

- Acrylic/cotton

**Material**

- PVC

**Metatarsal Protection**

- NA

**Metatarsal Protection**

- None

**Sizes**

- Men's sizes 3 - 15

**Steel Midsole Protection**

- NA

**Steel Midsole Protection**

- None

**Steel Toe Protection**

- NA

**Steel Toe Protection**

- Style # 75109 has steel toe protection

**Tread**

- NA

**Tread**

- TDT outsole

**Waterproof**

- No

**Waterproof**

- Yes

**Technical Support**

Technical Support is available Monday through Friday, 8:00 AM to 7:00 PM EST. 1.800.873.5242  
hsptechsupport@honeywell.com